



# Hydropad Portable Wash Pads

No Permits No Design Cost No Construction No Delays

Are The Answer!

ENGINEERING





## HYDROPAD, PORTABLE WASH PAD

## Hydropad Features:

- Standard size is 8' X 8', 10', 12' or 14'
- Connect multiple pads together
- Support from 12 to 30 tons
- Available with clean out feature
- Optional splash panels
- Optional drive up ramps

#### Benefits:

- Instant wash pad
- Completely portable
- No construction required
- Extremely flexible. (If you need a pad that is 14' X 80' then you set (10) Hydropads end to end



### Specifications:

Dimension -- each pad is 8'L X 8',10',
 12' or 14'W X12"H

#### How it Works:

The Hydropad is an instant fix for anyone that needs a wash pad but doesn't want to spend the time or money to get building permits, architectural design, and everything else that goes with a concrete wash pad. Set the Hydropad in place, or multiple Hydropads if that fits your requirement, make the simple connections and start washing. They are not only a wash pad but the perfect containment system for a complete water filtration or recirculation system.

Item #	Weight Capacity (last number in item # is ton rating)	Size
HP-8-12	Available in 12, 16, 25, and 30 ton ratings	8' X 8'
HP-10-12	Available in 12, 16, 25, and 30 ton ratings	8' X 10'
HP-12-12	Available in 12, 16, 25, and 30 ton ratings	8' X 12'
HP-14-12	Available in 12, 16, 25, and 30 ton ratings	8' X 14'

#### **Suggested Accessories**

**HPHS-SG** 

**HPHS-SGS** 

**HPHS-SGW** 

HP-RAMP

**HPHS-SP** 

HPHS-PB

ST-36-A

**HESC** 

HP-C Hydropad connector clip (includes 3 clips)

HP-HOSE

HP-CAP

Connection hose to connect fluid between Hydropads
Cap to plug off unused Hydropad connection ports
HP-SP-4X2, OR (4X4), (2X6) OR (4X6)
Splash panel (example: 4x2 = 4' high X 2' wide)
Splash panel end stiffener (for 4' or 6' panels)

High solids side gutter

High solids side gutter

High solids side gutter seal kit (for connecting multiple side gutters)

High solids side gutter weirs. (Weirs help solids settle into side gutters)

Drive up equipment ramp Submersible pump Sump pump strainer basket

Sump cleaning attachment (hooks to pressure washer)

Sludge Cart

1. Specifications are effective August 2001. 2. Specifications are subject to change without notice.



865 West 2600 South, Salt Lake City, UT 84119 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

## Hydropad Specifications

	12 tons			16 tons			25 tons			30 tons		
	PART#	SIZE	WEIGHT									
Γ	HS-8-12	8'X 8'	1,646	HS-8-16	8' x 8'	1,709	HS-8-25	8' x 8'	1,847	HS-8-30	8' x 8'	1,969
	HS-10-12	8' x 10'	2,009	HS-10-16	8' x 10'	1,924	HS-10-25	8' x 10'	2,367	HS-10-30	8' x 10'	2,489
	HS-12-12	8' x 12'	2,353	HS-12-16	8' x 12'	2,520	HS-12-25	8' x 12'	2,714	HS-12-30	8' x 12'	2,835
	HS-14-12	8' x 14'	2,826	HS-14-16	8' x 14'	2,953	HS-14-25	8' x 14'	3,005	HS-14-30	8' x 14'	3,406

#### Required Equipment & Accessories

HPHS-SG	High solids side gutter 8' long, one required for each Hydropad
HPHS-SGS	Gutter seal kit, includes (2) bulkhead fittings, (4) fasteners, (1) end plug
HPHS-SGP	Pipe connection kit (1) bulkhead fitting, (1) 1-1/2" nipple, allows gravity drain
HPHS-PB	Sump pump protection basket for use in side gutter
HPHS-SP	Hydropad high solids sump pump & fitting

of pad to determine square footage of rolling rain tarp).

#### Optional Equipment & Accessories

		• • • •	
HPHS-SG HPHS-CG HPHS-SG HP-RAMP HP-TREAI HP-CJ-8 HP-C-10 HP-C-11 HP-C-12 HP-C-14 1027521	w	High solids side gutter 8' long and 2' wide, one required for earligh solids center gutter 8' long, one required between two H High solids side gutter weir, slows water down allowing incread Drive up equipment ramp, 2' wide, 90" long 2' X 8' expanded metal tread plate End Connector on center gutter pad * Connector cap to join Hydropads end to end (all are 8') Connector cap to join Hydropads side to side (8) Connector cap to join Hydropads side to side (10') Connector cap to join Hydropads side to side (12') Connector cap to join Hydropads side to side (14') 1500 watt floating side gutter heater	ydropads
HPW4 HPW6 HPW8 HPW10 HPW12 HPW14	4' walls 6' walls 8' walls 10' walls 12' walls 14' walls	Hydropad wall sections; (select the height you want and then determine the length based on how many sides you want walls on).	
HPRT		Hydropad rolling rain tarp; (multiply length of pad by width	

<sup>\*</sup> If more than one Hydropad is required, a connector cap to join Hydropads end to end is required for the connection of each two Hydropads.

NO PERMITS, NO DESIGN COSTS, NO CONSTRUCTION AND NO DELAYS, just an instant wash pad! Hydropad portable wash pads are designed to hold machinery and equipment up to 30 tons (60,000 lbs.) per axle. Hydropads are constructed using 5 gauge C channel skirts, 7 gauge A channel drive on surfaces and 12 gauge shedding plates. Each pad is 100% enamel dipped and oven dried with a non-skid surface rolled onto each A channel. They are available in 12, 16, 25 and 30 ton/axle models. HOW THEY WORK: On a level surface of dirt, gravel, asphalt or concrete, one or more Hydropad units can be set in place and will collect fluid for disposal or recycling in any Hydrokleen filtration system. Multiple Hydropads can be joined to make large wash pad areas. High solids Hydropads drain fluid and debris to a side gutter system. Gutters come in 10" and 24" wide sizes. The larger size is for heavier solids collection. The gutters also come with lids and one removable weir per gutter. Wall sections are available and are galvanized steel in sizes from 4' to 12' in height. Ramps for entry and exit are available as well. A rolling rain tarp is also available for easy covering in case of dust or rain events. Assembly requires a forklift and a two man crew. Surface preparation is simple.



865 West 2600 South, Salt Lake City, UT 84119 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265